

892LT / 894LT LEARNING REMOTE CONTROLS

Single remote control solution
for gated communities.



892LT

894LT

KEY FEATURES

INDEPENDENT BUTTON PROGRAMMING

Allows for different frequency and codes

VERSATILE COMPATIBILITY

Eliminate multiple remotes

SMART

EASY TO PROGRAM.

INDEPENDENT BUTTON PROGRAMMING ALLOWS FOR DIFFERENT FREQUENCY AND CODES: SECURITY+ 2.0® (TRI-BAND 310/315/390 MHZ), SECURITY+® 315 MHZ AND SECURITY+ 390 MHZ.

ELIMINATES THE NEED FOR MULTIPLE REMOTES WHEN OPERATING LIFTMASTER® GARAGE DOOR OPENERS, GATE OPERATORS, COMMERCIAL DOOR OPERATORS OR MYQ® ACCESSORIES.

CLONING CAPABILITY OF EXISTING LIFTMASTER DIP SWITCH REMOTE CONTROLS (61LM AND 361LM) OR A LIFTMASTER ENCRYPTED DIP SWITCH REMOTE CONTROL (811LM) TO ANY BUTTON.

RELIABLE

COMPATIBLE WITH LIFTMASTER SECURITY+ 2.0 TRI-BAND (310, 315 AND 390 MHZ) AND SECURITY+ GARAGE DOOR OPENERS, GATE OPERATORS, COMMERCIAL DOOR OPERATORS AND COMMERCIAL RECEIVERS.

SECURE

FLEXIBLE COMPATIBILITY WITH DIRECT PROGRAMMING TO SECURITY+ 2.0 AND SECURITY+ ROLLING CODE TECHNOLOGY FOR SECURITY AND DEPENDABILITY.

TOTAL SOLUTION ACCESSORIES:

SECURITY+ 2.0 UNIVERSAL RECEIVER

Three-channel commercial receiver provides enhanced range, security and dependability. Compatible with all Security+ 2.0 Remote Controls.



850LM

SECURITY+ 2.0 WEATHERPROOF UNIVERSAL RECEIVER

Three-channel commercial receiver provides enhanced range, security and dependability in a weathertight housing for extra protection. Compatible with all Security+ 2.0 Remote Controls.



860LM

SECURITY+ 2.0 COMMERCIAL HIGH-CAPACITY RECEIVER

High-capacity commercial receiver provides enhanced range, security and dependability. Holds up to 1,000 Security+ 2.0 Remote Controls. Compatible with all Security+ 2.0 Remote Controls.



STAR1000

SECURITY+ 2.0 SINGLE BUTTON ENCRYPTED DIP SWITCH REMOTE CONTROL

Single button visor remote control programs directly to the Security+ 2.0 gate operator receiver for master access and used to clone to the learning remote controls for gate access.



811LM

SINGLE BUTTON DIP SWITCH REMOTE CONTROLS

Single button visor remote controls in 390 MHz and 315 MHz frequencies. DIP Switch programming directly to an existing LiftMaster commercial receiver for master access and used to clone to the learning remote control for gate access.



61LM / 361LM

PRODUCT GUIDE

892LT / 894LT

LEARNING REMOTE CONTROLS

LiftMaster®

